



3400 MOWER



RUGGED, LOW MAINTENANCE TRAILED MOWERS

FOR TOPPING AND MOWING HAY AND SILAGE



QUALITY PRODUCTS BUILT TO LAST



technical specifications

3400



CUTTING WIDTH	3.40 metres (11'2")
NUMBER OF ROTORS	4
NUMBER OF DOUBLE EDGE BLADES	12
POWER REQUIREMENT (AT 540 rpm)	60kw (80 HP)
BLADE SPEED	320 kph
TRACTOR LINKAGE	Trailed
HEIGHT ADJUSTMENT	25-300mm
TYRES	10.0/75 X 15.3
WEIGHT	1180kg (2620lbs)
MIN. HYDRAULIC PRESSURE REQUIRED	900psi



Hydraulic Suspension

Hydraulic suspension and shock absorption using accumulator.

Adjust topping height hydraulically to preset settings.

Pressure gauge standard fitment.

Large agricultural tyres.

Multiple Settings

Transport hydraulic lock out standard.

Offset mower position set hydraulically.

Cutting height from 25mm to 300mm.

Robust quality construction.

8 drawbar settings.

Low maintenance belt and gearbox combination drive train

High blade speed for cutting heavy swath.

Stone guards standard feature.

Cutting and transport width 3.4m (11'2").

New design high tensile drums ensure long working life.

Enquire now from your authorised dealer



FOR YOUR NEAREST DEALER AND
FURTHER INFORMATION CONTACT

NEW ZEALAND

REESE ENGINEERING LTD.
PALMERSTON NORTH, NEW ZEALAND
TEL: (06) 357-9323
FAX: (06) 354-3155
EMAIL: reese@reese.co.nz
WEBSITE: www.reeseagri.com

AUSTRALIA

REESE ENGINEERING LTD.
GEELONG, VICTORIA, AUSTRALIA
FREEPHONE: 1-800-140-196
FREEFAX: 1-800-140-195
EMAIL: reese@reese.co.nz
WEBSITE: www.reeseagri.com

USA

REESE AGRI USA
P.O. BOX 128, BRAYMER,
MO, 64624, USA
TOLL FREE: 800-432-4020
FAX: (660) 645-2214
EMAIL: reese@reese.co.nz
WEBSITE: www.reeseagri.com