Model 4511Wrap-A-Matic In-line Round Bale Wrapper







Hydraulic controls are at a convenient height for ease of operation. Hydra park valve is standard on our self-propelled model.

The right choice

- Seals in flavor and nutrients
- Makes top quality haylage that is high in protein, with excellent feeding value
- Highly recommended by feed companies



13 HP electric start Honda engine. Easy access to refill gas tank and service engine.

Where craftsmanship, quality & trust still count

Wrap high moisture bales or dry hay



Model 4511 Wrap watch standard

- The Model 4511 In-line Bale Wrapper was designed and built for the contractor and farmer looking for reliable, dependable, efficient wrapping. The rigid tubular frame ensures a solid machine under heavy bales of haylage. Wrapping is fully automatic, or you can wrap manually. Hydra steering is manually operated.
- Hydraulic ramp folds down for wrapped hay discharge.
- Compact and rigid machine.
- Guide arms are adjustable for various size bales.
- Raise the hitch with the Hydra cylinder to drive into your tractor or vehicle hitch to tow. Lower the machine to ground for braking and stability during wrapping.
- Simple and easy to use.
- One person operation.
- Wrapping, testing and balancing your quality hay can really pay big dollars.
- Fast wrapping.





Contact:

TIGERCO DISTRIBUTING COMPANY BRAYMER, MO 64624 800-432-4020 tigerco@centurytel.net www.tigercoinc.com



Aluminum plate for clean out. Simple to operate.



2-30" Film tensioners. Cage swings open for easy loading of wrap.

Specifications

Bale sizes: 4'x4' to 5'x5'

Work lights

Highway lights: Plug into your tractor

or vehicle

Tires: 11L x 15 x 6 lug wheel

Drive wheel tire size: 23 x 8.5

Transport length: 13'9"

Unfolded length: 18'

Wheel width: 7'5"

Cage width: 8'9"

Height of machine: 8'4"

Approximate weight: 3740 lb.

Options: JD Green • Remote Control Steering • Remote Control Shutoff

Manufactured by



Made in Lancaster County, PA